

Heavy Duty Commercial Concrete Pressure Pump Business For Sale

Basic Information

- Place of Origin:
- Brand Name:
- Model Number:
- Minimum Order Quantity: 1
- Price: U F

Hunan

Sunny

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

HBT30
1 set
USD5000-7000 PER SET
FULL CONTAINER
20-35DAYS
L/C, D/P, T/T, Western Union
500 SET PER MONTH



Product Specification

- Application:
- Warranty:
- Model:
- Highlight:

concrete	•		• /	sale
	• •	busin		sale

Concrete Pump, Trailer Pump

3 Voare



More Images



High Performance Heavy Duty Commercial Hbt 30 Concrete Pump Singapore Product Description

The HBT30 concrete pump is a specific model within the HBT series of concrete pumps. It is a trailer-mounted concrete pump that is widely used in construction projects for the efficient transportation and placement of concrete. The HBT30 is known for its compact size, versatility, and reliable performance, making it a popular choice for small to medium-sized construction projects.

Key features and specifications of the HBT30 concrete pump include:

Trailer-Mounted Design: The HBT30 concrete pump is mounted on a trailer, providing excellent mobility and easy transportation between different job sites. Its compact size allows for maneuverability in tight spaces and facilitates quick setup and movement within the construction site.

Pumping System: The HBT30 is equipped with a hydraulic piston pumping system that delivers the necessary pressure to transport the concrete through the delivery pipeline. This system ensures a smooth and consistent flow of concrete, allowing for precise placement and reducing the risk of blockages.

Maximum Output and Pressure: The HBT30 concrete pump has a maximum output capacity of 30 cubic meters per hour (39 cubic yards per hour) and a maximum pumping pressure of 10 MPa (1450 psi). These specifications make it suitable for a wide range of construction applications, including residential, commercial, and light industrial projects.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Die sel engine	Electric/Die sel engine	Electric/Dies el engine	Electric/Dies el engine	Electric/Dies el engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Мра	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feedin g Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40

Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*	mm	3800*1500	4500*1500	5100*1700*	6400*2100*	6400*2100*2
H)		*1600	*1650	2000	2200	200

Product Features:

 Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.

4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.

	SENBI Hunan Sunny Intelliger	nt Machinery Co.,LTD.
& +86 191	18921276 amy@hnsunny.com.cr	n 🥑 sunnyconcretebatchingplant.com
Construction I	Machinery Supporting Industrial Park, High-	tech Zone, Ningxiang City, Hunan Province