



Portable Concrete Mixer With Pump Mobile For Construction

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: T6
- Minimum Order Quantity: 1 set
- Price: USD18000-25000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump
- After-sales Service Provided: Online Support
- Highlight: portable concrete pump,
portable concrete mixer with pump,
mobile concrete mixer with pump



Product Description

Portable Concrete Mixer and Pump Mobile Concrete Pump Mixer portable concrete mixer and pump For Construction **Portable Concrete Mixer and Pump** is the newest products patented by our company, it is combined by the traditional concrete pump and the mixer together, it is the most suitable for use in four to six floor buildings, especially in the group buildings, bridges, and the spread of small construction sites where need the concrete mixer at the scene.



Main Features

- 1) Simple structure in linear type ,easy in installation and maintanation.
- 2) Adopting advanced world famous brand components in pneumatic parts ,electric parts and operation parts.
- 3) High pressure double crank to control the die opening and closing.
- 4) Running in a high automatization and intellectualization,no pollution
- 5) Apply a linker to connect with the air conveyor ,which can directly inline with filling machine.

Item	HBTS30R	HBTS40R	HBTS60R	HBTS80-13R	HBTS90-16R
Theoretical Displacement(m ³ /h)	30	40/26	60/38	80/73	90/50
Maximum Outlet pressure(Mpa)	10	10/6	12/7	13/7.5	16/9

Max. Conveying distance V.H.	140/600	140/600	160/800	180/900	260/1000
Engine Power(kw)	62.5	62.5	82	129	146
Delivery Cylinder Bore *Stroke(mm)	160*1000	160*1300	180*1300	200*1650	200*1800
Main Cylinder Bore *Stroke(mm)	100*1000	100*1300	110*1300	125*1650	140*1800
High And Low Voltage Switching	No	Have	Have	Have	Have
Hydraulic Tank Volume(l)	300	350	400	50	500
Hopper Volume (l)	90	90	115	230	230
Fuel Tank Volume(m ³)	0.4	0.4	0.5	0.8	0.8
Maximum Aggregate Material Diameter(mm)	20	40	50	50	50
Feeding Height(mm)	1250	1250	1300	1450	1450
L*W*h(mm)	4600*1750 *2200	4800*1750 *2200	5000*2100 *2260	5900*2000 *2260	6000*2000*22 60
Host Quality(kg)	3700	390	4100	6300	6500



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province