

Wet Mix Concrete Batch Plant Automatic Small 25 35 50 75 90 120 180 M3/H

Basic Information

Place of Origin: Hunan
Brand Name: SUNNY
Model Number: HSZ50
Minimum Order Quantity: 1 set

Price: USD 11000-15000/ SET

Packaging Details: containerDelivery Time: 25-30 days

• Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



Product Specification

Maaterial: Cement, Crushed Stone, Sands And So On

Application: Building Works, Construction

Projects bridges dealer sirror

Projects, bridges, docks, airport

Control System: Automatic PLC Control,totally Automatic

• Productivity: ≤35m3/h

Mixer: JS750 Twin-shaft Concrete Mixer

Warranty: 12 MonthsCondition: New

 After-sales Service Engineers Available To Service Machinery Provided: Overseas, Online Support, Video Technical

Support, Field Installation, commissioning And

Training

• Highlight: wet mix concrete plant,

wet mix concrete batch plant,

wet batch concrete



Product Description

Siemens PLC control automatic small HZS 25 35 50 75 90 120 180 m3/H concrete wet batching plant Bucket type Concrete Mixing Plant 50m3/h Concrete Batching Plant

The HZS50 bucket type concrete mixing plant is an advanced and highly efficient batching plant designed for large-scale construction projects. It belongs to the family of bucket type batching plants, known for their precise measurement and reliable mixing capabilities. The HZS90 model specifically offers a range of features and benefits that make it a popular choice among construction professionals.

With a focus on productivity and quality, the HZS50 bucket type concrete mixing plant is designed to handle a substantial volume of concrete production. It is capable of producing 90 cubic meters of concrete per hour, making it suitable for medium to large construction projects such as highways, bridges, airports, and commercial buildings.

to large construction projects such as mg	ilways, bilages	, anponto, t		nai banan iga
Model	HZS35	HZS50	HZS75	HZS100
Production in Theory (m3/h)	35	50	75	100
Mixer Type	JS750	JS1000	JS1500	JS2000
Mixing Motor Power (KW)	2×15	2×18.5	2×30	2×37
Cycle time(S)	60	60	60	60
Mixer Discharging Volume(L)	750	1000	1500	2000
Maximum Particle Size of Aggregate(mm)60	60	60	80
Batching Volume(L)	1200	1600	2400	3200
Aggregate Species	2-3	2-4	4	4
Aggregate lifting motor power(kw)	7. 5	15	18.5	22
Discharging Height (m)	4	4	4	4
Installed Capacity(KW)	50	70	110	120



Features of concrete batching plant:

- 1.It adopts combined structure and unitized module, which is short, quick and very convenient for installation and demolition .
- 2. Increase the unloading angle of the aggregate bin to solve the problem of unloading difficulties caused by rain
- 3.It is convenient and quick to use the cylinder discharge or electric push rod to discharge.
- 4.The overall steel structure of the mixing station is made of high-quality steel, which has high overall structural strength and strong stability.
- 5.The mixing machine adopts the twin-shaft forced mixing main machine, which has strong mixing performance, uniform mixing and high productivity.
- 6.Excellent pneumatic components, electrical components, etc.; to ensure the reliability of the equipment, accurate metering performance.
- 7. Each maintenance and repair site is provided with a walking platform or a check ladder, and has sufficient operation space. Easy maintenance and repair 8. Environmental protection and energy saving, using pulse dust removal, recycling waste-water for reuse

与宣介智工 Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province