

Small Portable Concrete Batch Plant For Sale Ready Mix 75m3/H

Basic Information

Place of Origin: Hunan
Brand Name: SUNNY
Model Number: HSZ75
Minimum Order Quantity: 1 set

• Price: USD 110000-150000/ SET

Packaging Details: containerDelivery Time: 25-30 days

• Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



Product Specification

Maaterial: Cement, Crushed Stone, Sands And So On

• Application: Building Works, Construction

Projects, bridges, docks, airport

Control System: Automatic PLC Control,totally Automatic

• Productivity: ≤60m3/h

Mixer: JS1500 Twin-shaft Concrete Mixer

Warranty: 12 MonthsCondition: New

 After-sales Service Engineers Available To Service Machinery Provided: Overseas, Online Support, Video Technical

Overseas, Online Support, Video Technical Support, Field Installation, commissioning And

Training

• Highlight: portable concrete batch plant for sale,

portable concrete batch plant,

portable batch plant



Product Description

Small Portable Concrete Mixing Plant Ready Mix 75m3/h Concrete Batching Plant High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant

Belt Conveyor Type Concrete Batching Plant mainly consists of 5 major systems such as mixer, material weighing system, material conveying system, material storage system and control system and other ancillary facilities. It is equipped with the storage, batching, conveying, stirring, control and other devices of various raw materials required for precast concrete, and various aggregates, powders, admixtures, water, etc. A complete set of equipment for supplying concrete in a concentrated manner than by a mixer.

pecification

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600- 2000)≤±2%	(700-2400)≤±2%	(1000- 3600)≤±2%	(1600- 4800)≤±2%	(1600- 4800)≤±2%
Measuring range and precision of cement	(300- 1200)≤±1%	(300-1200)≤±1%	600- 1800)≤±1%	(800- 2400)≤±1%	(800- 2400)≤±1%
Measuring range and precision of coal ash	(200- 600)≤±1%	(200-600)≤±1%	(300- 900)≤±1%	(400- 1200)≤±1%	(400- 1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200- 700)≤±1%	(360- 1200)≤±1%	(360- 1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



Capacity: The HZS75 model is designed to handle a substantial volume of concrete production. With a capacity to produce 75 cubic meters of concrete per hour, it is well-suited for medium-sized construction projects that require a consistent supply of concrete.

Precise Measurement: The use of individual buckets for ingredient measurement ensures accurate proportions of cement, aggregate, water, and additives. This precise measurement system guarantees the production of high-quality concrete with consistent strength and durability.

Customization: The HZS75 plant can be easily customized to meet specific project requirements. It allows adjustments in the bucket capacity, ingredient quantities, and overall plant layout. This flexibility enables the plant to be tailored to the unique needs of medium-sized construction projects.

Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province