



Fully Automatic Small Lift Mini Concrete Batching Plant Hopper

Basic Information

- Place of Origin: Hunan
- Brand Name: SUNNY
- Model Number: HSZ90
- Minimum Order Quantity: 1 set
- Price: USD 110000-150000/ SET
- Packaging Details: container
- Delivery Time: 25-30 days
- Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Maaterial: Cement, Crushed Stone, Sands And So On
- Application: Building Works,Construction Projects,bridges,docks,airport
- Control System: Automatic PLC Control,totally Automatic
- Productivity: $\leq 90\text{m}^3/\text{h}$
- Mixer: JS1500 Twin-shaft Concrete Mixer
- Warranty: 12 Months
- Condition: New
- After-sales Service Provided: Engineers Available To Service Machinery Overseas,Online Support,Video Technical Support,Field Installation,commissioning And Training
- Highlight: **fully automatic batching plant, concrete batching plant hopper, mini concrete batching plant**



Product Description

Automatic small HZS25 HZS35 HZS50 HZS75 HZS90 hopper lift mini concrete batching plant concrete mixing plant
HZS90 Manufacturer Concrete Batch Plant concrete batching plant

Belt Conveyor Type Concrete Batching Plant mainly consists of 5 major systems such as mixer, material weighing system, material conveying system, material storage system and control system and other ancillary facilities. It is equipped with the storage, batching, conveying, stirring, control and other devices of various raw materials required for precast concrete, and various aggregates, powders, admixtures, water, etc. A complete set of equipment for supplying concrete in a concentrated manner than by a mixer.

pecification

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600-2000)≤±2%	(700-2400)≤±2%	(1000-3600)≤±2%	(1600-4800)≤±2%	(1600-4800)≤±2%
Measuring range and precision of cement	(300-1200)≤±1%	(300-1200)≤±1%	600-1800)≤±1%	(800-2400)≤±1%	(800-2400)≤±1%
Measuring range and precision of coal ash	(200-600)≤±1%	(200-600)≤±1%	(300-900)≤±1%	(400-1200)≤±1%	(400-1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200-700)≤±1%	(360-1200)≤±1%	(360-1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



Features of concrete batching plant:

Control System: The control system of the HZS75 plant can be tailored to meet the project's needs. It can be equipped with advanced automation features, such as computerized control panels, programmable logic controllers (PLCs), and user-friendly interfaces. The control system can be customized to include specific monitoring and data logging capabilities, allowing for efficient operation and quality control.

Auxiliary Equipment: Additional auxiliary equipment can be integrated into the HZS75 plant based on project requirements. This may include cement silos, screw conveyors, water storage tanks, additive dispensers, and admixture systems. The integration of auxiliary equipment can enhance the efficiency and functionality of the batching plant.

Mobility Options: Depending on the project's nature, the HZS75 plant can be customized to offer mobility options. It can be designed as a stationary plant for long-term projects or as a mobile plant mounted on wheels or trailers for projects that require frequent relocation.



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province