Hunan Sunny Intelligent Machinery Co.,LTD. sunnyconcretebatchingplant.com

50m3/H To 100m3/H Cement Concrete Batching Plant Concrete Mixer 100t 200t Cement Silos

Basic Information

Place of Origin: Hunan
Brand Name: SUNNY
Model Number: HSZ100
Minimum Order Quantity: 1 set

• Price: USD 110000-150000/ SET

Packaging Details: containerDelivery Time: 25-30 days

• Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



Product Specification

Maaterial: Cement, Crushed Stone, Sands And So On

• Application: Building Works, Construction

Projects, bridges, docks, airport

Control System: Automatic PLC Control,totally Automatic

• Productivity: ≤60m3/h

Mixer: JS2000 Twin-shaft Concrete Mixer

Warranty: 12 MonthsCondition: New

 After-sales Service Engineers Available To Service Machinery Provided: Overseas, Online Support, Video Technical

Support, Field Installation, commissioning And

Training

• Highlight: concrete batch plant,

batching plant concrete mixer,

cement mixing plant



Product Description

Bucket type Full automatic hzs50m3/h to 100m3/h oncrete batching and mixing plant with 100t 200t cement silos **High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant**

One of the key advantages of the HZS60 model is its use of individual buckets for ingredient measurement. This ensures accurate proportions of cement, aggregate, water, and additives, resulting in consistent and high-quality concrete. The buckets are equipped with precise measurement systems, such as load cells or volumetric mechanisms, to ensure precise and reliable dosing of each ingredient.

The HZS60 bucket type concrete batching plant incorporates a central mixing unit, which can be a stationary drum mixer, a twin-shaft mixer, or a planetary mixer. These mixers employ advanced technology to ensure thorough blending of the ingredients, resulting in a homogeneous mixture with optimal strength and durability.

Model	HZS35	HZS50	HZS75	HZS100
Production in Theory (m3/h)	35	50	75	100
Mixer Type	JS750	JS1000	JS1500	JS2000
Mixing Motor Power (KW)	2×15	2×18.5	2×30	2×37
Cycle time(S)	60	60	60	60
Mixer Discharging Volume(L)	750	1000	1500	2000
Maximum Particle Size of Aggregate(mm)	60	60	60	80
Batching Volume(L)	1200	1600	2400	3200
Aggregate Species	2-3	2-4	4	4
Aggregate lifting motor power(kw)	7. 5	15	18.5	22
Discharging Height (m)	4	4	4	4
Installed Capacity(KW)	50	70	110	120



Features of concrete batching plant:

- 1.It adopts combined structure and unitized module, which is short, quick and very convenient for installation and demolition .
- 2. Increase the unloading angle of the aggregate bin to solve the problem of unloading difficulties caused by rain
- 3.It is convenient and quick to use the cylinder discharge or electric push rod to discharge.
- 4.The overall steel structure of the mixing station is made of high-quality steel, which has high overall structural strength and strong stability.
- 5. The mixing machine adopts the twin-shaft forced mixing main machine, which has strong mixing performance, uniform mixing and high productivity.
- 6.Excellent pneumatic components, electrical components, etc.; to ensure the reliability of the equipment, accurate metering performance.
- . 7.Each maintenance and repair site is provided with a walking platform or a check ladder, and has sufficient operation space. Easy maintenance and repair 8.Environmental protection and energy saving, using pulse dust removal, recycling waste-water for reuse

5≡กัย Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn

sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province