

50 to 240 m3/h mini cement batching plant ready sicoma mixer mixing mobile concrete batch plant

Basic Information

Place of Origin: Hunan
Brand Name: SUNNY
Model Number: HSZ75
Minimum Order Quantity: 1 set

• Price: USD 110000-150000/ SET

Packaging Details: containerDelivery Time: 25-30 days

Payment Terms:
 L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



Product Specification

Maaterial: Cement, Crushed Stone, Sands And So On

• Application: Building Works, Construction

Projects, bridges, docks, airport

Control System: Automatic PLC Control,totally Automatic

• Productivity: ≤60m3/h

Mixer: JS1500 Twin-shaft Concrete Mixer

Warranty: 12 MonthsCondition: New

 After-sales Service Engineers Available To Service Machinery Provided: Overseas, Online Support, Video Technical

Overseas, Online Support, Video Technical Support, Field Installation, commissioning And

Training

• Highlight: mobile concrete batching plant,

mini cement batching plant, 240 m3/h cement batching plant



Product Description

High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant

The HZS75 batching plant is a versatile and efficient concrete mixing plant that is widely used in construction projects, including roads, bridges, buildings, and other infrastructure. It belongs to the HZS series of stationary concrete batching plants, known for their reliability and high productivity.

The HZS75 batching plant is designed to produce a uniform and high-quality concrete mixture. It has a theoretical production capacity of 60 cubic meters per hour, making it suitable for medium to large-scale construction projects. The plant is equipped with advanced technology and components to ensure precise measurement and control of materials, resulting in consistent and accurate concrete mixes.

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600- 2000)≤±2%	(700-2400)≤±2%	(1000- 3600)≤±2%	(1600- 4800)≤±2%	(1600- 4800)≤±2%
Measuring range and precision of cement	(300- 1200)≤±1%	(300-1200)≤±1%	600- 1800)≤±1%	(800- 2400)≤±1%	(800- 2400)≤±1%
Measuring range and precision of coal ash	(200- 600)≤±1%	(200-600)≤±1%	(300- 900)≤±1%	(400- 1200)≤±1%	(400- 1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200- 700)≤±1%	(360- 1200)≤±1%	(360- 1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



与三方智工 Hunan Sunny Intelligent Machinery Co.,LTD.









