

## Premixed Asphalt Plant 80t/H Stationary Asphalt Mixing **Plant**

## **Basic Information**

. Place of Origin: Hunan . Brand Name: Sunny LB1000 Model Number: Minimum Order Quantity:

• Price: USD250,000-50,0000 PER SET

**FULL CONTAINER** Packaging Details:

. Delivery Time: 20-35DAYS

• Payment Terms: L/C, T/T, Western Union, MoneyGram

Supply Ability: 50 SET PER MONTH



## **Product Specification**

· Warranty: 1 Year

After-sales Service Engineers Available To Service Machinery Provided:

Overseas

Asphalt Mixing Plant Type:

· Application: High-grade Asphalt Road

Paving, Construction Areas, Road Construction Asphalt Plant

. Control System: PLC+colorized Touching Screen

• Highlight: premixed Asphalt Plant,

80t/h Asphalt Mixing Plant, **Stationary Asphalt Mixing Plant** 



## **Product Description**

premixed Asphalt Plant 80t/h Stationary Asphalt Mixing Plant

The LB1000 asphalt mixing plant offers a range of features that make it a popular choice for various construction projects. Here are some of the typical features of an LB1000 asphalt mixing plant:

Energy Efficiency and Environmental Considerations: The plant is designed to be energy-efficient, minimizing energy consumption and reducing environmental impact. It may feature advanced dust collection systems to capture and filter out dust and particulate matter, ensuring compliance with environmental regulations and promoting a clean working environment. User-Friendly Design: The LB1000 model is designed with user convenience in mind. It features user-friendly controls and a well-organized layout, making it easy for operators to monitor and control the asphalt production process. The intuitive interface and clear display enhance operational efficiency.

Durability and Reliability: The LB1000 asphalt mixing plant is built with high-quality materials and components to ensure durability and long service life. It is designed to withstand demanding operating conditions and deliver reliable performance over an extended period.

over all extended period.									
Model	Rated Output	Capacit v	Dust removal effect	ľ	Fuel consumpti on	Fire coal		Capacity	Dryer Size
LB100 0			≤20 mg/Nm³	264k w	5.5-7 kg/t	10kg/t	aggregate; ±5‰	4×0.5111	φ1.75m×7 m
		1300kg		264k w			powder; ±2.5‰	4×0.5111	φ1.75m×7 m
LB150 0	120t/h	1500kg		325k w				4×0.5111°	φ1.75m×7 m
LB200 0	160t/h	2000kg		483k w			asphalt; ±2.5‰	DX IZIII°	φ1.75m×7 m





**与三力智工** Hunan Sunny Intelligent Machinery Co.,LTD.



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province