

80TPH Batch Mix Asphalt Plant Bitumen Batch Mix Plant **Manufacturers**

Basic Information

. Place of Origin: Hunan Brand Name: Sunny LB1000 Model Number: Minimum Order Quantity:

• Price: USD250,000-50,0000 PER SET

FULL CONTAINER Packaging Details:

. Delivery Time: 20-35DAYS

• Payment Terms: L/C, T/T, Western Union, MoneyGram

Supply Ability: 50 SET PER MONTH



Product Specification

· Warranty: 1 Year

After-sales Service Engineers Available To Service Machinery Provided:

Overseas

Asphalt Mixing Plant Type:

· Application: High-grade Asphalt Road

Paving, Construction Areas, Road Construction Asphalt Plant

. Control System: PLC+colorized Touching Screen

. Highlight: asphalt batch plants,

asphalt batch plant manufacturers,

bitumen batch mix plant

Product Description

80TPH New Batch Mix Asphalt Plant ZAP-S80 Bitumen Plant Price

Production Capacity: The 80tph asphalt mixer plant has a production capacity of 80 tons per hour. This capacity allows for efficient completion of medium-sized projects, such as rural road construction, parking lots, and small-scale infrastructure development.

Mixing System: The plant typically incorporates a twin-shaft paddle mixer or a drum mixer. The mixing system ensures thorough blending of aggregates, filler, and bitumen, resulting in a high-quality asphalt mixture with excellent consistency and

Precise Measurement and Control: The 80tph asphalt mixer plant is equipped with accurate weighing systems that ensure precise dosing of aggregates, filler, and bitumen. The control system allows for adjustments in mixing ratios and temperature settings, enabling the production of various asphalt mix designs while maintaining consistent quality.

Energy Efficiency and Environmental Considerations: The plant is designed to be energy-efficient, minimizing energy consumption and reducing environmental impact. It may include advanced dust collection systems to capture and filter out dust and particulate matter, ensuring compliance with environmental regulations and promoting a clean working environment. These are some of the typical characteristics of an 80tph asphalt mixer plant. However, it's important to note that specific features and specifications may vary depending on the manufacturer and model. It is recommended to refer to the product catalogs or directly contact asphalt plant manufacturers for detailed information on a particular 80tph asphalt mixer plant.

			Dust	Total	Fuel	Fire	Weighing	Honnor	
liviodel	Output		removal effect	ľ	Iconsumpti	l		Hopper Capacity	Dryer Size
1.5400		У	eneci		OH				
LB100	80t/h	1000kg		264k			aggregate;	4×8.5m³	φ1.75m×7
0		l		w			±5‰		m
LB130	1.00±/b	1300kg		264k				4×8.5m³	φ1.75m×7
0	1001/11	TSOURG		w			lpowder:	4x0.3111	m
LB150	120±/h	15001/0	≤20	325k	5.5-7 kg/t	10ka/t	±2.5‰	4×8.5m³	φ1.75m×7
0	120011	TSOURG	J	w	3.3-7 kg/t			4×0.3111°	m
LB200	160±/h	2000kg		483k			asphalt;	5×12m³	φ1.75m×7
0	1001/11	ZUUUKG		w			±2.5‰	DX IZIII°	m m

















