

120T/H Stationary Hot Mix Asphalt Plant Batching Bitumen Mixing **Plant**

Basic Information

. Place of Origin: Hunan . Brand Name: Sunny LB1500 Model Number: Minimum Order Quantity:

• Price: USD250,000-50,0000 PER SET

FULL CONTAINER Packaging Details:

. Delivery Time: 20-35DAYS

• Payment Terms: L/C, T/T, Western Union, MoneyGram

Supply Ability: 50 SET PER MONTH



Product Specification

· Warranty: 1 Year

After-sales Service Engineers Available To Service Machinery Provided:

Overseas

Asphalt Mixing Plant Type:

· Application: High-grade Asphalt Road

Paving, Construction Areas, Road Construction Asphalt Plant

. Control System: PLC+colorized Touching Screen

• Highlight: hot mix asphalt plant, hot mix batching plant,

hot mix bitumen plant



Product Description

LB1500 120T/H Stationary Hot Mix Asphalt Plant Bitumen Mixing Plant Price

The asphalt plant adopts modular design, easy installation and maintenance, fast removal and transportation. It is mainly used for the construction of highways, highways, municipal roads, airports and ports.

Energy Efficiency and Environmental Considerations: The LB1500 asphalt plant features advanced dust collection systems that effectively capture and filter out dust and particulate matter, ensuring compliance with environmental regulations and promoting a clean working environment. The plant is designed to be energy-efficient, minimizing energy consumption and reducing environmental impact.

User-Friendly Design: The LB1500 model is designed with user convenience in mind. It features user-friendly controls and a well-organized layout, allowing operators to monitor and control the asphalt production process easily. The intuitive interface and clear display enhance operational efficiency and reduce the learning curve for plant operators.

Versatility: The LB1500 asphalt plant is versatile and can handle various asphalt production requirements. It can produce a wide range of asphalt mix designs to meet different project specifications, making it suitable for a variety of construction applications.

Durability and Reliability: The LB1500 model is constructed with high-quality materials and components, ensuring its durability and reliability. It is designed to withstand demanding operating conditions and deliver consistent performance over an extended period.

Model	Rated Output	Capacit v	Dust removal effect	ľ	Fuel consumpti on	Ι.		Сараспу	Dryer Size
LB100 0				264k w	5.5-7 kg/t	10kg/t	aggregate; ±5‰	4x0.3111	φ1.75m×7 m
		1300kg		264k w			powder; ±2.5‰	4×6.5111°	φ1.75m×7 m
LB150 0	120t/h	1500kg	mg/Nm³	325k w				4x0.5111	φ1.75m×7 m
LB200 0	160t/h	2000kg		483k w			asphalt; ±2.5‰	DX IZIII°	φ1.75m×7 m















