

Batch Mix Asphalt Plant 120TPH Bitumen Mixture Machine Stationary Asphalt **Plant**

Basic Information

. Place of Origin: Hunan Brand Name: Sunny LB1500 Model Number: Minimum Order Quantity:

• Price: USD250,000-50,0000 PER SET

FULL CONTAINER Packaging Details:

. Delivery Time: 20-35DAYS

• Payment Terms: L/C, T/T, Western Union, MoneyGram

Supply Ability: 50 SET PER MONTH



Product Specification

· Warranty: 1 Year

After-sales Service Engineers Available To Service Machinery Provided:

Overseas

Asphalt Mixing Plant Type:

· Application: High-grade Asphalt Road

Paving, Construction Areas, Road Construction Asphalt Plant

. Control System: PLC+colorized Touching Screen

. Highlight: stationary asphalt plant, Asphalt Plant 120TPH,

plant asphalt



Product Description

Batch Mix Asphalt Plant 120TPH Bitumen Mixture Machine

One of the key features of the LB1500 model is its precise and efficient mixing system. It utilizes a twin-shaft paddle mixer, which ensures thorough blending of aggregates, filler, and bitumen. This results in a high-quality asphalt mixture with excellent uniformity and consistency, meeting the required specifications for road surfaces.

The LB1500 asphalt plant incorporates advanced technology for precise measurement and control. It is equipped with a highly accurate weighing system that ensures precise dosing of aggregates, filler, and bitumen. The control system allows for the adjustment of mixing ratios and temperature settings, providing flexibility to produce various asphalt mix designs.

High Production Capacity: The LB1500 model boasts a production capacity of 160 tons per hour, making it ideal for large-scale asphalt production. Its high capacity allows for efficient completion of projects, especially those involving highways, airports, and major road construction.

Superior Mixing Performance: The LB1500 asphalt plant utilizes a twin-shaft paddle mixer, which ensures thorough and uniform mixing of aggregates, filler, and bitumen. This results in a high-quality asphalt mixture with excellent consistency and uniformity, providing superior performance on road surfaces.

Precise Measurement and Control: The LB1500 plant is equipped with advanced weighing systems that ensure accurate and precise dosing of aggregates, filler, and bitumen. The control system allows for adjustments in mixing ratios and temperature settings, providing flexibility to produce various asphalt mix designs with consistent quality.

Model	Rated Output	Capacit v	Dust removal effect	ľ	Fuel consumpti on	Ι.		Capacity	Dryer Size
LB100 0	l		≤20 mg/Nm³	264k w	5.5-7 kg/t	10kg/t	aggregate; ±5‰	4x0.3111	φ1.75m×7 m
LB130 0	100t/h	1300kg		264k w			powder; ±2.5‰	4x0.3111	φ1.75m×7 m
LB150 0	120t/h	1500kg		325k w				4×6.5111°	φ1.75m×7 m
LB200 0	160t/h	2000kg		483k w			asphalt; ±2.5‰	DX IZIII°	φ1.75m×7 m















