

160tph asphalt hot mix equipment price

Basic Information

. Place of Origin: Hunan Brand Name: Sunny LB2000 Model Number: . Minimum Order Quantity: 1 set

• Price: USD250,000-50,0000 PER SET

FULL CONTAINER Packaging Details:

. Delivery Time: 20-35DAYS

• Payment Terms: L/C, T/T, Western Union, MoneyGram

Supply Ability: 50 SET PER MONTH



Product Specification

· Warranty: 1 Year

After-sales Service Engineers Available To Service Machinery Provided:

Overseas

Asphalt Mixing Plant Type:

· Application: High-grade Asphalt Road

Paving, Construction Areas, Road Construction Asphalt Plant

PLC+colorized Touching Screen . Control System:

• Highlight: 160tph asphalt hot mix equipment,

hot mix asphalt batch plant, hot mix asphalt equipment



Product Description

The LB2000 asphalt plant is a highly efficient and reliable asphalt mixing plant designed for large-scale asphalt production. It is part of the LB series of asphalt plants, known for their advanced technology and superior performance. The LB2000 model specifically offers a range of features and capabilities that make it a popular choice among asphalt producers.

The LB2000 asphalt plant is designed to handle a substantial volume of asphalt production. It has a production capacity of 160 tons per hour, making it suitable for medium to large-scale projects such as highways, airports, and major road construction. The asphalt plant adopts modular design, easy installation and maintenance, fast removal and transportation. It is mainly used for the construction of highways, highways, municipal roads, airports and ports.

- 1. Modular design and integrity steel base, reasonable layout, demolition, transportation and installation faster and easier.
- 2. Superior drying drum plate design, and independent research and development of advanced combustion heating technology to improve efficiency, reduce energy consumption.
- 3. Plus high hot aggregate bin design to increase the stock of hot aggregate storage, to increase producing capacity.
- 4. Automatic/manual control system with failure self-diagnosis program, simple and safe.
- 5. Core components adopt international famous brand products, such as Siemens electrical components, EBICO burners, Switzerland METTLER TOLEDO weighing sensor, etc., reduces the failure rate and prolong its service life.

Model	Rated Output	Capacit v	Dust removal effect	ľ	Fuel consumpti on	Ι.		Capacity	Dryer Size
LB100 0	l .			264k w			aggregate; ±5‰	4x0.3111	φ1.75m×7 m
		1300kg		264k w			bowder:	4×0.3111°	φ1.75m×7 m
LB150 0	120t/h	1500kg	≤20 mg/Nm³	325k w	5.5-7 kg/t	l		4x0.3111	φ1.75m×7 m
LB200 0	160t/h	2000kg		483k w			asphalt; ±2.5‰	DX IZIII°	φ1.75m×7 m

















