



High Performance 160T Asphalt Concrete Plant For Sale

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: LB2000
- Minimum Order Quantity: 1 set
- Price: USD250,000-50,0000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50 SET PER MONTH



Product Specification

- Warranty: 1 Year
- After-sales Service Provided: Engineers Available To Service Machinery Overseas
- Type: Asphalt Mixing Plant
- Application: High-grade Asphalt Road Paving, Construction Areas, Road Construction Asphalt Plant
- Control System: PLC+colorized Touching Screen
- Highlight: **High Performance Asphalt Concrete Plant, Asphalt Concrete Plant For Sale, 160T Asphalt Concrete Plant**



Product Description

The LB2000 asphalt plant is designed with user convenience in mind. It features user-friendly controls and a well-organized layout, allowing operators to monitor and control the asphalt production process with ease. The plant is also equipped with safety features to ensure a secure working environment for the operators.



Furthermore, the LB2000 model offers flexibility in terms of customization. It can be tailored to meet specific project requirements, allowing adjustments in the configuration, layout, and auxiliary equipment. This adaptability ensures that the plant can efficiently handle diverse asphalt production needs.

In summary, the LB2000 asphalt plant is a robust and efficient solution for large-scale asphalt production. With its high production capacity, precise mixing system, advanced control technology, and user-friendly design, it enables the production of high-quality asphalt mixtures for a wide range of construction projects.

The asphalt plant adopts modular design, easy installation and maintenance, fast removal and transportation. It is mainly used for the construction of highways, highways, municipal roads, airports and ports.

1. Modular design and integrity steel base, reasonable layout, demolition, transportation and installation faster and easier.
2. Superior drying drum plate design, and independent research and development of advanced combustion heating technology to improve efficiency, reduce energy consumption.
3. Plus high hot aggregate bin design to increase the stock of hot aggregate storage, to increase producing capacity.
4. Automatic/manual control system with failure self-diagnosis program, simple and safe.
5. Core components adopt international famous brand products, such as Siemens electrical components, EBICO burners, Switzerland METTLER TOLEDO weighing sensor, etc., reduces the failure rate and prolong its service life.

Model	Rated Output	Mixer Capacity	Dust removal effect	Total power	Fuel consumption	Fire coal	Weighing accuracy	Hopper Capacity	Dryer Size
LB1000	80t/h	1000kg	≤20 mg/Nm³	264kw	5.5-7 kg/t	10kg/t	aggregate; ±5‰	4×8.5m³	φ1.75m×7m
LB1300	100t/h	1300kg		264kw			powder; ±2.5‰	4×8.5m³	φ1.75m×7m
LB1500	120t/h	1500kg		325kw				4×8.5m³	φ1.75m×7m
LB2000	160t/h	2000kg		483kw			asphalt; ±2.5‰	5×12m³	φ1.75m×7m



 +86 19118921276  amy@hnsunny.com.cn  sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province