



## Cement Mini Concrete Pumps Truck Tractor Portable Line Electric Small Concrete Hose

Our Product Introduction

for more products please visit us on [sunnyconcretebatchingplant.com](http://sunnyconcretebatchingplant.com)

### Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT50
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



### Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT50
- Highlight: mini concrete pump, mini cement pump, concrete pump truck



## Product Description

Mini concrete pumps truck Hbt 50 Tractor portable line Electric Small concrete hose Concrete Pump

### Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorporated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force. they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



| Parameters                        | Unit     | HBT30.6.3<br>5S                | HBT40.8.4<br>5S                | HBT50.10.5<br>5S               | HBT60.13.9<br>0S               | HBT80.16.11<br>0S              |
|-----------------------------------|----------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Type of Power Machine             | /        | Electric/Diesel engine         | Electric/Diesel engine         | Electric/Diesel engine         | Electric/Diesel engine         | Electric/Diesel engine         |
| Pumping Volume(Max)               | m³/h     | 30                             | 35                             | 52                             | 66                             | 75                             |
| Outlet Pressure                   | Mpa      | 6                              | 8                              | 10                             | 13                             | 13                             |
| Hydraulic System Type             | /        | Open                           | Open                           | Open                           | Open                           | Open                           |
| High/Low Switch                   | /        | Rotary Valve                   | Rotary Valve                   | Rotary Valve                   | Rotary Valve                   | Rotary Valve                   |
| Rater Power                       | kw       | 35                             | 45                             | 55                             | 90                             | 90                             |
| Distribution Valve Type           | /        | S Valve                        | S Valve                        | S Valve                        | S Valve                        | S Valve                        |
| Concrete Cylinder Diameter*Stroke | mm       | Φ125*600                       | Φ140*1000                      | Φ200*1000                      | Φ200*1650                      | Φ200*1800                      |
| Hopper Capacity*Feeding Height    | L*m<br>m | 350*1000                       | 350*1100                       | 600*1400                       | 600*1400                       | 600*1400                       |
| Max.Aggregate Size                | mm       | Pebble:20;<br>Crushed Stone:20 | Pebble:20;<br>Crushed Stone:20 | Pebble:50;<br>Crushed Stone:40 | Pebble:50;<br>Crushed Stone:40 | Pebble:50;<br>Crushed Stone:40 |
| Total Weight                      | kg       | 2300                           | 2500                           | 4500                           | 6000                           | 6100                           |
| Dimension(L*W*H)                  | mm       | 3800*1500*1600                 | 4500*1500*1650                 | 5100*1700*2000                 | 6400*2100*2200                 | 6400*2100*2200                 |

### Product Features:

1. Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
2. Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
3. The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.
4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;
5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.

---

 +86 19118921276     amy@hnsunny.com.cn     sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province