



Cement Concrete Pump Machine Prices Diesel Engine Electric Trailer Mounted Stationary Concrete Pump

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT30
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT30
- Highlight: cement concrete pump, concrete pump machine, stationary Concrete Pump



Product Description

cement concrete pump machine prices diesel engine electric trailer mounted stationary Hbt 30 Concrete Pump

Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorporated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force. they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve	S Valve	S Valve	S Valve	S Valve
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200

Product Features:

Hopper Capacity: The hopper of the HBT30 can hold a sufficient amount of concrete, enabling continuous pumping without

frequent reloading. The hopper capacity is typically around 0.4 to 0.6 cubic meters (14 to 21 cubic feet), ensuring efficient workflow and minimizing downtime.

Delivery Pipeline: The HBT30 concrete pump is connected to a delivery pipeline that transfers the concrete from the hopper to the desired location. The length and diameter of the delivery pipeline can be customized to meet the specific needs of the project, allowing for flexible placement options.

Control System: The HBT30 is equipped with a user-friendly control system that enables operators to adjust the pumping parameters, monitor the pumping process, and ensure safe and efficient operation. The control system provides real-time information on the pumping pressure, flow rate, and other essential parameters, allowing for precise control and optimization of the concrete placement.

Power Source: The HBT30 concrete pump can be powered by either a diesel engine or an electric motor, depending on the requirements and conditions of the construction site. The choice of power source provides flexibility and allows for efficient operation in various environments.



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province