Heavy Duty Commercial Concrete Pump Placer Pouring

Basic Information

Place of Origin: Hunan
Brand Name: Sunny
Model Number: HBT30
Minimum Order Quantity: 1 set

Price: USD5000-7000 PER SETPackaging Details: FULL CONTAINER

• Delivery Time: 20-35DAYS

Payment Terms: L/C, D/P, T/T, Western Union
 Supply Ability: 500 SET PER MONTH



Product Specification

Application: Concrete Pump, Trailer Pump

Warranty: 3 YearsModel: HBT30

• Highlight: concrete placer pump, concrete placing pump,

concrete pouring pump



Product Description

High Performance Heavy Duty Commercial Hbt 30 Concrete Pump Singapore Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorportated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Die sel engine	Electric/Die sel engine	Electric/Dies el engine	Electric/Dies el engine	Electric/Dies el engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Мра	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Ф125*600	Ф140*1000	Ф200*1000	Φ200*1650	Ф200*1800
Hopper Capacity*Feedin g Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W* H)	mm	3800*1500 *1600	4500*1500 *1650	5100*1700* 2000	6400*2100* 2200	6400*2100*2 200

Product Features:

The HBT30 concrete pump offers several advantages in concrete placement:

Compact and Maneuverable: The compact size of the HBT30 makes it suitable for construction sites with limited space or restricted access. Its maneuverability allows for easy navigation through narrow pathways and congested areas. Versatility: The HBT30 concrete pump can handle various types of concrete mixes, including low slump, high slump, and lightweight concrete. It is suitable for a wide range of applications, such as foundations, slabs, walls, and more. Precise Placement: The HBT30 allows for precise and controlled concrete placement, even in challenging or hard-to-reach areas. It provides flexibility in construction projects, accommodating different heights and distances. Reliability and Durability: The HBT30 is designed to withstand the demanding conditions of construction sites. Its sturdy construction and high-quality components ensure long-lasting performance and reliable operation. User-Friendly Operation: The HBT30 is designed with user-friendly features that make it easy to operate and maintain. Its intuitive control system and accessible components simplify the pumping process and reduce downtime. The HBT30 concrete pump is a versatile and reliable solution for concrete placement in small to medium-sized construction projects. Its compact design, high performance, and ease of operation make it a valuable asset for contractors and construction companies seeking efficient and cost-effective concrete pumping capabilities.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province