



30m3/H 45kw Diesel Engine Portable Trailer Mounted Concrete Pump Machine Concrete Transfer Pump

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT30
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT30
- Highlight: portable concrete pump,
trailer mounted concrete pump,
concrete transfer pump



Product Description

30m³/h 45kw diesel engine portable trailer mounted concrete pump machine concrete transfer pump

Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorporated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force. they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine
Pumping Volume(Max)	m ³ /h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve	S Valve	S Valve	S Valve	S Valve
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200

Product Features:

Pumping Capacity: The HBT30 concrete pump has a maximum output capacity of 30 cubic meters per hour (39 cubic yards

per hour). This means that it can pump up to 30 cubic meters of concrete in one hour, making it suitable for small to medium-sized construction projects.

Pumping Pressure: The HBT30 has a maximum pumping pressure of 10 MPa (1450 psi). This pressure allows for the efficient transportation of concrete through the delivery pipeline, ensuring a smooth and consistent flow during the placement process.

Vertical Pumping Distance: The HBT30 can achieve a vertical pumping distance of up to 100 meters (328 feet). This specification refers to the height at which the concrete can be pumped vertically from the ground level to an elevated location, such as upper floors or high-rise structures.



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province