



## High Speed Concrete Mini Pump Automatic Concrete Conveyor Pump

Our Product Introduction

for more products please visit us on [sunnyconcretebatchingplant.com](http://sunnyconcretebatchingplant.com)

### Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT30
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



### Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT30
- Highlight: Concrete Mini Pump, Automatic concrete pump, concrete conveyor pump



## Product Description

### HBT30 Concrete Pump High- Speed Concrete Mini Pump Automatic Concrete Conveying Pump

#### Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorporated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force. they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve	S Valve	S Valve	S Valve	S Valve
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200

#### Product Features:

Horizontal Pumping Distance: The HBT30 is capable of horizontal pumping over a distance of up to 300 meters (984 feet).

This specification indicates the maximum distance the concrete can be pumped horizontally from the pump to the desired location on the construction site.

**Aggregate Size:** The HBT30 concrete pump can handle aggregates with a maximum size of up to 30 mm (1.18 inches). This specification refers to the largest particles or stones that can pass through the pump without causing blockages or damage to the pumping system.

**Engine Power:** The HBT30 can be powered by either a diesel engine or an electric motor, depending on the specific model and requirements. The power source provides the necessary energy to drive the pumping system and ensure efficient concrete placement.

**Control System:** The HBT30 is equipped with a user-friendly control system that allows operators to adjust various pumping parameters, such as pumping speed and pressure. The control system provides real-time monitoring and feedback on the pumping process, enabling precise control and optimization.

It's important to note that specific specifications and performance may vary slightly depending on the manufacturer and model of the HBT30 concrete pump. It's recommended to refer to the manufacturer's documentation or consult with suppliers to obtain the precise specifications for a particular HBT30 model.



**Hunan Sunny Intelligent Machinery Co.,LTD.**



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province