

Small Mini Cement Mortar Truck Concrete Pump Hbt 40 Mini Truck Machines Chinese

Basic Information

- Place of Origin:
- Brand Name:
- Model Number:
- Minimum Order Quantity:Price:
- Packaging Details: FULL CON
- Delivery Time:
- Payment Terms:
- Supply Ability:
- HBT40 1 set USD5000-7000 PER SET FULL CONTAINER 20-35DAYS L/C, D/P, T/T, Western Union 500 SET PER MONTH

Hunan

Sunny



Product Specification

- Application:
- Warranty:

Model:Highlight:

- Concrete Pump,Trailer Pump 3 Years HBT40
- truck concrete pump, concrete pump truck for sale, chinese concrete pump



Small Mini Cement Mortar Concrete Pump Hbt 40 Mini truck machines Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorportated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force.they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Die sel engine	Electric/Die sel engine	Electric/Dies el engine	Electric/Dies el engine	Electric/Dies el engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Мра	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feedin g Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W* H)	mm	3800*1500 *1600	4500*1500 *1650	5100*1700* 2000	6400*2100* 2200	6400*2100*2 200

Product Features:

Hopper Capacity: The hopper of the HBT40 can hold a sufficient amount of concrete, allowing for continuous pumping without frequent reloading. The hopper capacity is typically around 0.6 to 0.7 cubic meters (21 to 25 cubic feet), ensuring efficient workflow and minimizing downtime.

Delivery Pipeline: The HBT40 concrete pump is connected to a delivery pipeline that transfers the concrete from the hopper to the desired location. The length and diameter of the delivery pipeline can be customized to meet the specific requirements of

the project, allowing for flexible placement options.

Control System: The HBT40 is equipped with a user-friendly control system that enables operators to adjust the pumping parameters, monitor the pumping process, and ensure safe and efficient operation. The control system provides real-time information on the pumping pressure, flow rate, and other essential parameters, allowing for precise control and optimization of the concrete placement.

Power Source: The HBT40 concrete pump can be powered by either a diesel engine or an electric motor, depending on the specific needs and conditions of the construction site. The choice of power source provides flexibility and allows for efficient operation in various environments.

	Hunan Sunny Intelligent Machinery Co.,LTD.	
+86 19118921276	amy@hnsunny.com.cn 🕑 sunnyconcretebatchingplant.com	
Construction Machinery	Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province	