



High Pressure Concrete Mixer Hydraulic Pump For Concrete Pump In Dubai

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT40
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT40
- Highlight: concrete mixer hydraulic pump, concrete mixer and pump, concrete mix and pump



Product Description

Hbt 40 High Pressure Pump for Concrete Machine Concrete Pump in Dubai

Product Description

The HBT40 concrete pump offers several advantages in concrete placement:

High Efficiency: With its maximum output capacity of 40 cubic meters per hour, the HBT40 enables fast and continuous concrete pumping, improving construction productivity and meeting project deadlines.

Versatility: The HBT40 concrete pump is suitable for a wide range of concrete mixes, including low slump, high slump, and lightweight concrete. It can be used in various applications, such as foundations, slabs, walls, and more.

Precise Placement: The HBT40 allows for accurate and controlled concrete placement, even in challenging or hard-to-reach areas. It provides flexibility in construction projects, accommodating different heights and distances.

Durability and Reliability: The HBT40 is built to withstand the demanding conditions of construction sites. Its robust construction and high-quality components ensure long-lasting performance and reliability.

Operator-Friendly Design: The HBT40 is designed with user-friendly features that make it easy to operate and maintain. Its intuitive control system and accessible components simplify the pumping process and reduce downtime.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve	S Valve	S Valve	S Valve	S Valve
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200

Product Features:

1. Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
2. Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
3. The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.
4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;
5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province