



Small Trailer-Mounted Concrete Pump Cement Pump Trailer 60m³/H

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT60
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT60
- Highlight: Concrete Pump 60m³/h,
small trailer concrete pump for sale,
cement pump trailer for sale



Product Description

Factory Price Cheap Trailer-mounted Concrete Pump 60m³/h

Product Description

The HBT series concrete pump is a type of trailer-mounted concrete pump that is widely used in construction projects for efficient and reliable concrete placement. It is designed to transport liquid concrete from the mixing site to the desired location, offering high performance, versatility, and ease of operation.

Key features and components of the HBT series concrete pump include:

Trailer-Mounted Design: The HBT series concrete pump is mounted on a trailer, providing mobility and ease of transportation between different job sites. The trailer design allows for quick and convenient setup, as well as easy movement within the construction site.

Pumping System: The pumping system of the HBT series concrete pump consists of a hydraulic piston or a rotary pump. This system generates the necessary pressure to transport the concrete through the delivery pipeline. The pumping system ensures a smooth and consistent flow of concrete, enabling precise placement.

Hopper: The HBT series concrete pump features a hopper that receives the concrete from a mixer truck or other source. The hopper acts as a temporary storage space for the concrete before it is pumped into the delivery pipeline. It is equipped with a stirring device to prevent the concrete from settling or segregating during the pumping process.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine				
Pumping Volume(Max)	m ³ /h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve				
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40

Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200

Product Features:

1. Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
2. Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
3. The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.
4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;
5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.



Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276 amy@hnsunny.com.cn sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province