

Pipe Concrete Line Pump For Sale 100m 60m

Basic Information

Place of Origin: Hunan
Brand Name: Sunny
Model Number: HBT60
Minimum Order Quantity: 1 set

Price: USD5000-7000 PER SETPackaging Details: FULL CONTAINER

• Delivery Time: 20-35DAYS

Payment Terms: L/C, D/P, T/T, Western Union
 Supply Ability: 500 SET PER MONTH



Product Specification

Application: Concrete Pump, Trailer Pump

Warranty: 3 YearsModel: HBT60

• Highlight: concrete line pump, concrete pump 100m,

concrete pump 60m



Product Description

concrete pump HBT60 concrete mortar pump with price pipe concrete pump Product Description

HBT series concrete pumps are excellent modernized concrete machinery developed with aid of advanced technology. They are high tech concrete machine which are incorportated with international advanced technology and experiences in designing to replace the traditional way to lift the concrete by labor force they adopt the diesel engine drive and motor drive S valve pump and gate valve pump with excellent technical performance, high standard configuration and high reliability.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Die sel engine	Electric/Die sel engine	Electric/Dies el engine	Electric/Dies el engine	Electric/Dies el engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Мра	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Ф125*600	Ф140*1000	Ф200*1000	Ф200*1650	Ф200*1800
Hopper Capacity*Feedin g Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W* H)	mm	3800*1500 *1600	4500*1500 *1650	5100*1700* 2000	6400*2100* 2200	6400*2100*2 200

Product Features:

Delivery Pipeline: The concrete pump is connected to a delivery pipeline that transfers the concrete from the hopper to the desired location. The pipeline is typically made of high-quality and durable materials to withstand the pressure and abrasion

caused by the flowing concrete. It can be extended and adjusted to reach different heights and distances as required by the construction project.

Control System: The HBT series concrete pump is equipped with a user-friendly control system that allows operators to adjust the pumping parameters, monitor the pumping process, and ensure safe and efficient operation. The control system provides real-time information on the pumping pressure, flow rate, and other essential parameters, enabling precise control and optimization of the concrete placement.

Diesel or Electric Engine: The concrete pump is powered by either a diesel engine or an electric motor, depending on the model and specific requirements. Diesel engines provide greater mobility and are suitable for remote or off-grid construction sites, while electric motors offer a more environmentally friendly and quieter operation.

与三方智工 Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province