

# 60m3/H Big Concrete Pump Machine For High Rise Building Hydraulic Stationary Trailer

## **Basic Information**

Place of Origin: Hunan
Brand Name: Sunny
Model Number: HBT60
Minimum Order Quantity: 1 set

Price: USD5000-7000 PER SETPackaging Details: FULL CONTAINER

• Delivery Time: 20-35DAYS

Payment Terms: L/C, D/P, T/T, Western Union
 Supply Ability: 500 SET PER MONTH



# **Product Specification**

Application: Concrete Pump, Trailer Pump

Warranty: 3 YearsModel: HBT60

Highlight: concrete pump for high rise building,

concrete pump machine, big concrete pump



#### **Product Description**

concrete pump 60m3/h Concrete Hydraulic Stationary Concrete Trailer Pump Product Description

The HBT series concrete pump offers several advantages in concrete placement:

High Efficiency: The HBT series concrete pump provides a high pumping capacity, allowing for rapid and continuous concrete placement. It helps to improve construction productivity and meet tight project schedules.

Versatility: The concrete pump can handle various types of concrete mixes, including low slump, high slump, and lightweight concrete. It is suitable for a wide range of applications, such as foundations, slabs, walls, and more.

Precise Placement: The HBT series concrete pump enables precise and accurate placement of concrete, even in challenging or hard-to-reach areas. It allows for vertical, horizontal, and overhead concrete pumping, providing flexibility in construction projects.

Reduced Labor and Material Wastage: By utilizing a concrete pump, manual labor required for concrete placement is minimized. The precise control of concrete flow also helps to reduce material wastage, resulting in cost savings. Improved Safety: The use of a concrete pump reduces the physical strain on workers, as it eliminates the need for manually transporting and placing concrete. It helps to create a safer working environment on the construction site.

The HBT series concrete pump is a reliable and efficient solution for concrete placement in construction projects. Its combination of mobility, high performance, and precise control makes it a valuable asset for contractors and construction companies seeking efficient and effective concrete pumping capabilities.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Die sel engine	Electric/Die sel engine	Electric/Dies el engine	Electric/Dies el engine	Electric/Dies el engine
Pumping Volume(Max)	m³/h	30	35	52	66	75
Outlet Pressure	Мра	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve				
Concrete Cylinder Diameter*Stroke	mm	Ф125*600	Ф140*1000	Ф200*1000	Ф200*1650	Ф200*1800
Hopper Capacity*Feedin g Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400

Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100
Dimension(L*W* H)	mm	3800*1500 *1600	4500*1500 *1650	5100*1700* 2000	6400*2100* 2200	6400*2100*2 200

## **Product Features:**

- 1. Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
- Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
   The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.
- 4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;
- 5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.





+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province