



Mortar Small Concrete Mixer And Pump Line Construction Diesel Mini Concrete Mixer Pump

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HBT60
- Minimum Order Quantity: 1 set
- Price: USD5000-7000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump, Trailer Pump
- Warranty: 3 Years
- Model: HBT60
- Highlight: small cement pump, small concrete line pump, small concrete mixer and pump



Product Description

HBT60 concrete mortar pump Small Construction Diesel Mini Concrete Mixer Pump Price Of Concrete Pump

Product Description

The HBT series concrete pump offers several advantages in concrete placement:

High Efficiency: The HBT series concrete pump provides a high pumping capacity, allowing for rapid and continuous concrete placement. It helps to improve construction productivity and meet tight project schedules.

Versatility: The concrete pump can handle various types of concrete mixes, including low slump, high slump, and lightweight concrete. It is suitable for a wide range of applications, such as foundations, slabs, walls, and more.

Precise Placement: The HBT series concrete pump enables precise and accurate placement of concrete, even in challenging or hard-to-reach areas. It allows for vertical, horizontal, and overhead concrete pumping, providing flexibility in construction projects.

Reduced Labor and Material Wastage: By utilizing a concrete pump, manual labor required for concrete placement is minimized. The precise control of concrete flow also helps to reduce material wastage, resulting in cost savings.

Its combination of mobility, high performance, and precise control makes it a valuable asset for contractors and construction companies seeking efficient and effective concrete pumping capabilities.



Parameters	Unit	HBT30.6.3 5S	HBT40.8.4 5S	HBT50.10.5 5S	HBT60.13.9 0S	HBT80.16.11 0S
Type of Power Machine	/	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine	Electric/Diesel engine
Pumping Volume(Max)	m ³ /h	30	35	52	66	75
Outlet Pressure	Mpa	6	8	10	13	13
Hydraulic System Type	/	Open	Open	Open	Open	Open
High/Low Switch	/	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve	Rotary Valve
Rater Power	kw	35	45	55	90	90
Distribution Valve Type	/	S Valve	S Valve	S Valve	S Valve	S Valve
Concrete Cylinder Diameter*Stroke	mm	Φ125*600	Φ140*1000	Φ200*1000	Φ200*1650	Φ200*1800
Hopper Capacity*Feeding Height	L*m m	350*1000	350*1100	600*1400	600*1400	600*1400
Max.Aggregate Size	mm	Pebble:20; Crushed Stone:20	Pebble:20; Crushed Stone:20	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40	Pebble:50; Crushed Stone:40
Total Weight	kg	2300	2500	4500	6000	6100

Dimension(L*W*H)	mm	3800*1500*1600	4500*1500*1650	5100*1700*2000	6400*2100*2200	6400*2100*2200
------------------	----	----------------	----------------	----------------	----------------	----------------

Product Features:

- 1. Agitation by the entire shaft axis design, embolization motor, strictly ensures the coaxial.
- 2. Double-loop open circuit hydraulic system, ensure fast direction switching speed and high efficiency
- 3. The distribution valve adopts the advanced S pipe valve system which consists of hard alloy eyeglass plates, cutting rings and rubber springs.
- 4. It has good sealing performance; the structure is simple and reliable, and convenient replacement of the wearing parts;
- 5. The pump is assembled through streamlined production with strictly control on the process to make sure its high quality.



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province