



## Small Concrete Mixer With Pump Hose Self-Loading Mixer

### Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: T6
- Minimum Order Quantity: 1 set
- Price: USD18000-25000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



### Product Specification

- Application: Concrete Pump
- After-sales Service Provided: Online Support
- Highlight: small concrete mixer with pump,  
small concrete mixer pump,  
concrete mixer pump



## Product Description

concrete mixer with pump mixer with hose pump self-loading mixer concrete pump

**Portable Concrete Mixer and Pump** is the newest products patented by our company, it is combined by the traditional concrete pump and the mixer together, it is the most suitable for use in four to six floor buildings, especially in the group buildings, bridges, and the spread of small construction sites where need the concrete mixer at the scene.



**Accessibility:** The concrete mixing pump can reach areas that are challenging to access with traditional concrete delivery methods. It is particularly useful in congested or restricted construction sites where space is limited or obstacles hinder the movement of concrete trucks.

**Cost Savings:** The concrete mixing pump reduces the need for manual labor and additional equipment, resulting in cost savings for construction projects. It also minimizes material wastage by allowing precise control over the amount of concrete needed for each application.

**On-Site Mixing:** With a concrete mixing pump, concrete can be mixed on-site, eliminating the need for the transportation of pre-mixed concrete. This ensures the availability of fresh concrete, which is essential for achieving high-quality and durable construction.

In conclusion, the concrete mixing pump is a versatile and efficient solution for mixing and delivering concrete at construction sites. Its integration of mixing and pumping functions provides numerous benefits in terms of productivity, convenience, and cost-effectiveness, making it a valuable asset for construction projects of various sizes and complexities.

Item	HBTS30R	HBTS40R	HBTS60R	HBTS80-13R	HBTS90-16R
------	---------	---------	---------	------------	------------

Theoretical Displacement(m³/h)	30	40/26	60/38	80/73	90/50
Maximum Outlet pressure(Mpa)	10	10/6	12/7	13/7.5	16/9
Max. Conveying distance V.H.	140/600	140/600	160/800	180/900	260/1000
Engine Power(kw)	62.5	62.5	82	129	146
Delivery Cylinder Bore *Stroke(mm)	160*1000	160*1300	180*1300	200*1650	200*1800
Main Cylinder Bore *Stroke(mm)	100*1000	100*1300	110*1300	125*1650	140*1800
High And Low Voltage Switching	No	Have	Have	Have	Have
Hydraulic Tank Volume(l)	300	350	400	50	500
Hopper Volume (l)	90	90	115	230	230
Fuel Tank Volume(m³)	0.4	0.4	0.5	0.8	0.8
Maximum Aggregate Material Diameter(mm)	20	40	50	50	50
Feeding Height(mm)	1250	1250	1300	1450	1450
L*W*h(mm)	4600*1750*2200	4800*1750*2200	5000*2100*2260	5900*2000*2260	6000*2000*2260
Host Quality(kg)	3700	390	4100	6300	6500



**Hunan Sunny Intelligent Machinery Co.,LTD.**



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province