



Mixer Cement Pump Mixer Mini

Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: T6
- Minimum Order Quantity: 1 set
- Price: USD18000-25000 PER SET
- Packaging Details: FULL CONTAINER
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 500 SET PER MONTH



Product Specification

- Application: Concrete Pump
- After-sales Service Provided: Online Support
- Highlight: mixer concrete pump, concrete pump mixer, cement mixer and pump



Product Description

beton mixer cement pump and mixer mini concrete pump with mixer

Portable Concrete Mixer and Pump

The concrete mixing pump offers several advantages over traditional methods of concrete mixing and transportation:

Efficiency and Time Savings: By combining the mixing and pumping functions, the concrete mixing pump eliminates the need for separate equipment and reduces the time required for concrete production and transportation. It allows for continuous and efficient concrete placement, enhancing project productivity.

Versatility: The concrete mixing pump is highly versatile and can handle a wide range of concrete mixes, including low slump, high slump, and lightweight concrete. It can be used for various applications such as foundations, slabs, walls, and even vertical and overhead placements.

Accessibility: The concrete mixing pump can reach areas that are challenging to access with traditional concrete delivery methods. It is particularly useful in congested or restricted construction sites where space is limited or obstacles hinder the movement of concrete trucks.

Cost Savings: The concrete mixing pump reduces the need for manual labor and additional equipment, resulting in cost savings for construction projects. It also minimizes material wastage by allowing precise control over the amount of concrete needed for each application.

On-Site Mixing: With a concrete mixing pump, concrete can be mixed on-site, eliminating the need for the transportation of pre-mixed concrete. This ensures the availability of fresh concrete, which is essential for achieving high-quality and durable construction.



Main Features

- 1) Simple structure in linear type ,easy in installation and maintanation.
- 2) Adopting advanced world famous brand components in pneumatic parts ,electric parts and operation parts.
- 3) High pressure double crank to control the die opening and closing.

- 4) Running in a high automatization and intellectualization,no pollution
 5) Apply a linker to connect with the air conveyor ,which can directly inline with filling machine.

Item	HBTS30R	HBTS40R	HBTS60R	HBTS80-13R	HBTS90-16R
Theoretical Displacement(m³/h)	30	40/26	60/38	80/73	90/50
Maximum Outlet pressure(Mpa)	10	10/6	12/7	13/7.5	16/9
Max. Conveying distance V.H.	140/600	140/600	160/800	180/900	260/1000
Engine Power(kw)	62.5	62.5	82	129	146
Delivery Cylinder Bore *Stroke(mm)	160*1000	160*1300	180*1300	200*1650	200*1800
Main Cylinder Bore *Stroke(mm)	100*1000	100*1300	110*1300	125*1650	140*1800
High And Low Voltage Switching	No	Have	Have	Have	Have
Hydraulic Tank Volume(l)	300	350	400	50	500
Hopper Volume (l)	90	90	115	230	230
Fuel Tank Volume(m³)	0.4	0.4	0.5	0.8	0.8
Maximum Aggregate Material Diameter(mm)	20	40	50	50	50
Feeding Height(mm)	1250	1250	1300	1450	1450
L*W*h(mm)	4600*1750*2200	4800*1750*2200	5000*2100*2260	5900*2000*2260	6000*2000*2260
Host Quality(kg)	3700	390	4100	6300	6500



Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn

sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province