



## 32M Concrete Placing Boom Floor Wedge

Our Product Introduction

for more products please visit us on [sunnyconcretebatchingplant.com](http://sunnyconcretebatchingplant.com)

### Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HG32
- Minimum Order Quantity: 1 set
- Price: USD6000-10000 PER SET
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50 SET PER MONTH



### Product Specification

- Condition: New
- Warranty: 1 Year
- After-sales Service Provided: Engineers Available To Service Machinery Overseas
- Application: Construction Engineering
- Keyword: Concrete Pump
- Highlight: **32M concrete placing boom, concrete placing boom for sale, placing boom concrete**



## Product Description

32M concrete placing boom Concrete Pouring Machine floor wedge for placing boom

A concrete placing pump is an innovative construction machine designed to transport and precisely place concrete at various locations on a construction site. It revolutionizes the process of concrete placement, offering increased efficiency, accuracy, and versatility compared to traditional methods. With its ability to pump concrete over long distances and to elevated heights, a concrete placing pump has become an essential tool in modern construction projects.

Concrete placing pumps consist of several key components, including a pump unit, a delivery pipeline, and a control system. The pump unit generates hydraulic pressure to propel the concrete through the pipeline, while the pipeline serves as the conduit for the concrete to flow from the pump to the desired location. The control system allows operators to regulate the pumping parameters and monitor the process, ensuring precise and efficient concrete placement.



Item	HG28	HG32
Max. Placing Radius (M)	27.5	32

Big Arm Length (M)	12.6	14.5
Big Arm Elevation (°)	0-65	0-65
Medium Arm Length (M)	8.8	9.2
Medium Arm Elevation (°)	0-180	0-180
Small Arm Length (M)	6.1	8
Small Arm Elevation (°)	0-180	0-180
Hose Length (M)	3	3
Concrete Delivery Pipe (Mm)	Ø125×6	Ø125×6
Tail Rotary Radius (M)	3.9	-
Total Power (Kw)	5.5	15
System Pressure (Mpa)	24	24
Rotary Speed (R/Min)	0.3-0.8	0.3-0.8
Rotary Range (°)	0-360	0-360
Lifting Speed (M/Min)	0.65	0.65
Lifting Height(M/Time)	≤3.6	≤3.6
Overall Height (M)	12.6	22.9
Bare Machine Weight (Kg)	10720	16700
Balance Weight(Kg)	4×2000	-
Control Mode	Panel/Wireless Remote Control	



**Hunan Sunny Intelligent Machinery Co.,LTD.**



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province