



## 28m Putzmeister Concrete Placing Boom Stationary

### Basic Information

- Place of Origin: Hunan
- Brand Name: Sunny
- Model Number: HG28
- Minimum Order Quantity: 1 set
- Price: USD6000-10000 PER SET
- Delivery Time: 20-35DAYS
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50 SET PER MONTH



### Product Specification

- Condition: New
- Warranty: 1 Year
- After-sales Service Provided: Engineers Available To Service Machinery Overseas
- Application: Construction Engineering
- Keyword: Concrete Pump
- Highlight: putzmeister concrete placing boom, placing boom for concrete pump, concrete placing boom putzmeister



## Product Description

### 28m concrete placing boom stationary putzmeister placing boom boom placer pump

The benefits of using a concrete placing pump are numerous. Firstly, it significantly improves productivity by delivering large volumes of concrete quickly and continuously. This reduces the reliance on manual labor and speeds up construction timelines. Secondly, a concrete placing pump enables precise placement of concrete, even in challenging or inaccessible areas. The operator can control the pumping speed, pressure, and flow rate, ensuring accurate positioning and minimizing material waste.

Moreover, concrete placing pumps offer versatility in handling different types of concrete mixes, including low slump, high slump, and lightweight concrete. They can be used for a wide range of construction applications, such as foundations, slabs, walls, columns, and even high-rise structures. The pumps are capable of pumping concrete both horizontally and vertically, allowing for flexibility in placement options and accommodating projects with varying elevation levels.



Item	HG28	HG32
------	------	------

Max. Placing Radius (M)	27.5	32
Big Arm Length (M)	12.6	14.5
Big Arm Elevation (°)	0-65	0-65
Medium Arm Length (M)	8.8	9.2
Medium Arm Elevation (°)	0-180	0-180
Small Arm Length (M)	6.1	8
Small Arm Elevation (°)	0-180	0-180
Hose Length (M)	3	3
Concrete Delivery Pipe (Mm)	Ø125×6	Ø125×6
Tail Rotary Radius (M)	3.9	-
Total Power (Kw)	5.5	15
System Pressure (Mpa)	24	24
Rotary Speed (R/Min)	0.3-0.8	0.3-0.8
Rotary Range (°)	0-360	0-360
Lifting Speed (M/Min)	0.65	0.65
Lifting Height(M/Time)	≤3.6	≤3.6
Overall Height (M)	12.6	22.9
Bare Machine Weight (Kg)	10720	16700
Balance Weight(Kg)	4×2000	-
Control Mode	Panel/Wireless Remote Control	



**Hunan Sunny Intelligent Machinery Co.,LTD.**



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province