

HZS60 Concrete Mixing Plant Dry Powder Mixing Plant Concrete Mixer With **Conveyor Belt**

Basic Information

- Place of Origin:
- Brand Name:
- Model Number: • Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- HSZ60 1 set USD 110000-150000/ SET container 25-30 days L/C, T/T, D/P, Western Union, MoneyGram 20 Set/Sets per Month



Product Specification

- Maaterial:
- Application:
- Control System:
- Productivity:
- Mixer:
- Warranty:
- Condition:
- After-sales Service Provided:
- Highlight:

- Cement, Crushed Stone, Sands And So On Building Works, Construction Projects, bridges, docks, airport
 - Automatic PLC Control,totally Automatic ≤60m3/h
 - JS1000 Twin-shaft Concrete Mixer
 - 12 Months

Hunan

SUNNY

- New
- Engineers Available To Service Machinery Overseas, Online Support, Video Technical Support, Field Installation, commissioning And Training
 - Dry Powder concrete mixing plant, Conveyor Belt Dry Powder Mixing Plant, concrete mixer with conveyor belt



More Images





Product Description

High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant

At the core of the HZS60 batching plant is a sophisticated mixing system that incorporates a twin-shaft concrete mixer. This twin-shaft mixer operates at a high speed, ensuring thorough and efficient mixing of aggregates, cement, water, and additives. The result is a homogeneous concrete mixture with excellent consistency and quality.

The HZS60 batching plant is equipped with advanced weighing systems that ensure precise measurement and dosing of materials. With precision sensors and load cells, these systems accurately weigh aggregates, cement, water, and additives. This precise control of material ratios guarantees consistent and high-quality concrete mixes.

Advantages of HZS60 Concrete Mixing Plant:

High production capacity: Meets the demands of large-scale construction projects. Excellent mixing quality: Produces consistent and high-quality concrete. Efficient operation: Minimizes downtime and maximizes productivity.

Durability and reliability: Built to withstand harsh conditions and provide long-lasting performance. **Customization options:** Can be tailored to specific project requirements.

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600- 2000)≤±2%	(700-2400)≤±2%	(1000- 3600)≤±2%	(1600- 4800)≤±2%	(1600- 4800)≤±2%
Measuring range and precision of cement	(300- 1200)≤±1%	(300-1200)≤±1%	600- 1800)≤±1%	(800- 2400)≤±1%	(800- 2400)≤±1%
Measuring range and precision of coal ash	(200- 600)≤±1%	(200-600)≤±1%	(300- 900)≤±1%	(400- 1200)≤±1%	(400- 1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200- 700)≤±1%	(360- 1200)≤±1%	(360- 1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



Features of concrete batching plant:

1.It adopts combined structure and unitized module, which is short, quick and very convenient for installation and demolition . 2.Increase the unloading angle of the aggregate bin to solve the problem of unloading difficulties caused by rain

3.It is convenient and quick to use the cylinder discharge or electric push rod to discharge.4.The overall steel structure of the mixing station is made of high-quality steel, which has high overall structural strength and strong stability.

5. The mixing machine adopts the twin-shaft forced mixing main machine, which has strong mixing performance, uniform mixing and high productivity.

 6.Excellent pneumatic components, electrical components, etc.; to ensure the reliability of the equipment, accurate metering performance. 7.Each maintenance and repair site is provided with a walking platform or a check ladder, and has sufficient operation space. Easy maintenance and repair 8.Environmental protection and energy saving, using pulse dust removal, recycling waste-water for reuse 				
	등= b월 Hunan Sunny Intelligent Machinery Co.,LTD.			
(🕒 +86 19118921276 🛛 🔄 amy@hnsunny.com.cn 🛛 🥲 sunnyconcretebatchingplant.com			
(Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province			