



HZS120 Stationary Concrete Batching Plant Automatic PLC Control for Bridges

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: SUNNY
- Model Number: HSZ120
- Minimum Order Quantity: 1 set
- Price: USD 110000-150000/ SET
- Packaging Details: container
- Delivery Time: 25-30 days
- Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Maaterial: Cement, Crushed Stone, Sands And So On
- Application: Building Works,Construction Projects,bridges,docks,airport
- Control System: Automatic PLC Control,totally Automatic
- Productivity: $\leq 120\text{m}^3/\text{h}$
- Mixer: JS2000 Twin-shaft Concrete Mixer
- Warranty: 12 Months
- Condition: New
- After-sales Service Provided: Engineers Available To Service Machinery Overseas,Online Support,Video Technical Support,Field Installation,commissioning And Training
- Highlight: **PLC Control Concrete Batching Plant, Stationary Concrete Batching Plant, Automatic Stationary Concrete Batching Plant**



More Images



Product Description

The HZS120 Stationary Concrete Batching Plant is a robust and reliable high-capacity solution designed to deliver high-quality concrete for large-scale construction projects. With a production rate of 120 cubic meters per hour, this plant features a dual-horizontal shaft mixer (JS2000) that ensures thorough and uniform mixing, essential for complex construction requirements. Engineered for durability and efficiency, the HZS120 plant is well-suited for infrastructure projects, commercial developments, and large industrial facilities requiring consistent concrete output.



Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600-2000)≤±2%	(700-2400)≤±2%	(1000-3600)≤±2%	(1600-4800)≤±2%	(1600-4800)≤±2%
Measuring range and precision of cement	(300-1200)≤±1%	(300-1200)≤±1%	600-1800)≤±1%	(800-2400)≤±1%	(800-2400)≤±1%
Measuring range and precision of coal ash	(200-600)≤±1%	(200-600)≤±1%	(300-900)≤±1%	(400-1200)≤±1%	(400-1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200-700)≤±1%	(360-1200)≤±1%	(360-1200)≤±1%

Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%
--	------------	-------------	--------------	--------------	--------------



Features of concrete batching plant:

High Production Capacity: The HZS120 batching plant has a theoretical production capacity of 120 cubic meters per hour, making it suitable for large-scale construction projects. It can handle high volumes of concrete production, allowing for efficient and timely completion of projects.

Excellent Mixing Performance: The HZS120 batching plant is equipped with a twin-shaft concrete mixer, which ensures thorough mixing of aggregates, cement, water, and additives. The twin-shaft mixer operates at a high speed, promoting efficient mixing and delivering a homogeneous concrete mixture.

Advanced Control System: The HZS120 batching plant is equipped with a sophisticated control system, allowing for precise control and monitoring of the mixing process. The control system offers features such as automatic weighing, accurate dosing, and real-time data monitoring. It enables operators to adjust various parameters and ensures consistent and high-quality concrete output.