



HZS120 Mobile Cement Concrete Mixing Plant Station For Airport Construction With Automatic PLC Control System

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: SUNNY
- Model Number: HSZ120
- Minimum Order Quantity: 1 set
- Price: USD 110000-150000/ SET
- Packaging Details: container
- Delivery Time: 25-30 days
- Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Maaterial: Cement, Crushed Stone, Sands And So On
- Application: Building Works,Construction Projects,bridges,docks,airport
- Control System: Automatic PLC Control,totally Automatic
- Productivity: $\leq 120\text{m}^3/\text{h}$
- Mixer: JS2000 Twin-shaft Concrete Mixer
- Warranty: 12 Months
- Condition: New
- After-sales Service Provided: Engineers Available To Service Machinery Overseas,Online Support,Video Technical Support,Field Installation,commissioning And Training
- Highlight: **HZS120 Mobile Cement Concrete Mixing Plant, HZS120 Mobile Cement Concrete Mixing Station , Airport Construction Concrete Mixing Plant**



More Images



Product Description

The **HZS120 Batching Plant** is a type of concrete mixing plant that is designed for high-output production and large-scale construction projects. It is capable of producing up to 120 cubic meters of high-quality concrete per hour, making it suitable for projects like highways, bridges, dams, and large commercial and residential developments.



Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600-2000)≤±2%	(700-2400)≤±2%	(1000-3600)≤±2%	(1600-4800)≤±2%	(1600-4800)≤±2%
Measuring range and precision of cement	(300-1200)≤±1%	(300-1200)≤±1%	600-1800)≤±1%	(800-2400)≤±1%	(800-2400)≤±1%
Measuring range and precision of coal ash	(200-600)≤±1%	(200-600)≤±1%	(300-900)≤±1%	(400-1200)≤±1%	(400-1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200-700)≤±1%	(360-1200)≤±1%	(360-1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



Features of concrete batching plant:

High Production Capacity: The HZS120 batching plant has a theoretical production capacity of 120 cubic meters per hour, making it suitable for large-scale construction projects. It can handle high volumes of concrete production, allowing for efficient and timely completion of projects.

Excellent Mixing Performance: The HZS120 batching plant is equipped with a twin-shaft concrete mixer, which ensures thorough mixing of aggregates, cement, water, and additives. The twin-shaft mixer operates at a high speed, promoting efficient mixing and delivering a homogeneous concrete mixture.

Advanced Control System: The HZS120 batching plant is equipped with a sophisticated control system, allowing for precise control and monitoring of the mixing process. The control system offers features such as automatic weighing, accurate dosing, and real-time data monitoring. It enables operators to adjust various parameters and ensures consistent and high-quality concrete output.



Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn

sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province