

# Hzs120 Fixed Concrete Batching Plant Engineering & Construction Machinery

### **Basic Information**

Place of Origin: Hunan
Brand Name: SUNNY
Model Number: HSZ120
Minimum Order Quantity: 1 set

• Price: USD 110000-150000/ SET

Packaging Details: containerDelivery Time: 25-30 days

Payment Terms:
 L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



# **Product Specification**

Maaterial: Cement, Crushed Stone, Sands And So On

 Application: Building Works, Construction Projects, bridges, docks, airport

Control System: Automatic PLC Control,totally Automatic

Productivity: ≤120m3/h

Mixer: JS2000 Twin-shaft Concrete Mixer

Warranty: 12 MonthsCondition: New

 After-sales Service Engineers Available To Service Machinery Provided: Overseas, Online Support, Video Technical

Overseas, Online Support, Video Technical Support, Field Installation, commissioning And

Training

• Highlight: Construction Machinery Concrete Batching

Plant

, Hzs120 Concrete Batching Plant, Fixed Concrete Batching Plant



# More Images



# **Product Description**

HZS120 CE ISO Certificated Concrete Batching Plant Construction High Quality 90m3 120m3 180m3 Ready Mixed Concrete Batch

#### Engineering & Construction Machinery HZS120 Fixed Concrete Batching Plant concrete mixing plant

Belt Conveyor Type Concrete Batching Plantmainly consists of 5 major systems such as mixer, material weighing system, material conveying system, material storage system and control system and other ancillary facilities. It is equipped with the storage, batching, conveying, stirring, control and other devices of various raw materials required for precast concrete, and various aggregates, powders, admixtures, water, etc. A complete set of equipment for supplying concrete in a concentrated manner than by a mixer.

#### pecification

**Capacity**: As the name suggests, the HZS120 can produce 120 cubic meters of concrete per hour, though its actual output may vary based on the mix design and other operational conditions.

**Batching System**: The plant is equipped with a fully automated aggregate batching system, which includes multiple aggregate bins, ensuring precise measurement and high accuracy in concrete production.

**Mixer**: The HZS120 typically uses a twin-shaft concrete mixer, which ensures uniform and high-quality mixing of concrete, ideal for both dry and wet mix designs. The twin-shaft design provides excellent homogeneity and efficient mixing.



| Name of parameter        | HZS60    | HZS90   | HZS120   | HZS180   | HZS240  |
|--------------------------|----------|---------|----------|----------|---------|
| Theoretical productivity | 60 M3/h  | 90 M3/h | 120 M3/h | 180 M3/h | 240m³/h |
| Model of mixer           | JS1000   | JS1500  | JS2000   | JS3000   | JS4000  |
| Mixing motor power       | 2x18.5Kw | 2x30Kw  | 2x37Kw   | 2x55Kw   | 2*75Kw  |
| Cycle period             | 60s      | 60s     | 60s      | 60s      | 60s     |
| Volume of mixer          | 1000L    | 1500L   | 2000L    | 3000L    | 4000L   |
| Unloading height         | 4.0m     | 4.0m    | 4.0m     | 4.0m     | 4.0m    |

| Measuring range and<br>precision of aggregate | (600-<br>2000)≤±2% | (700-2400)≤±2% | (1000-<br>3600)≤±2% | (1600-<br>4800)≤±2% | (1600-<br>4800)≤±2% |
|---|--------------------|----------------|---------------------|---------------------|---------------------|
| Measuring range and precision of cement       | (300-<br>1200)≤±1% | (300-1200)≤±1% | 600-<br>1800)≤±1%   | (800-<br>2400)≤±1%  | (800-<br>2400)≤±1%  |
| Measuring range and precision of coal ash     | (200-<br>600)≤±1%  | (200-600)≤±1%  | (300-<br>900)≤±1%   | (400-<br>1200)≤±1%  | (400-<br>1200)≤±2%  |
| Measuring range and precision of water        | 200-600)≤±1%       | (200-600)≤±1%  | (200-<br>700)≤±1%   | (360-<br>1200)≤±1%  | (360-<br>1200)≤±1%  |
| Measuring range and precision of admixture    | 20-60)≤±1%         | (20-60)≤±1%    | (30-100)≤±1%        | (36-120)≤±1%        | (36-120)≤±1%        |



#### Features of concrete batching plant:

Robust Construction and Durability: The HZS120 batching plant is built with high-quality materials and components, ensuring its durability and longevity. It is designed to withstand harsh working conditions and heavy-duty usage, making it suitable for long-term and continuous operation.

Flexible Configuration Options: The HZS120 batching plant offers flexibility in terms of configuration options. It can be customized to meet specific project requirements, such as the addition of multiple cement silos, admixture systems, and auxiliary equipment. This flexibility allows for the production of various types of concrete and accommodates specific project

Easy Maintenance and Service: The HZS120 batching plant is designed for easy maintenance and service. It incorporates features such as easy access to components, wear-resistant liners in the mixer, and user-friendly interfaces for monitoring and troubleshooting. These features contribute to reduced downtime and efficient maintenance operations.





+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province