## Hzs60 60 Cbm/H Ready Mixed Concrete Plant Twin-shaft Concrete Batching **Plant**

#### **Basic Information**

. Place of Origin: Hunan Brand Name: SUNNY HSZ60 Model Number: . Minimum Order Quantity:

• Price: USD 110000-150000/ SET

Packaging Details: container 25-30 days · Delivery Time:

Payment Terms: L/C, T/T, D/P, Western Union, MoneyGram

Supply Ability: 20 Set/Sets per Month



### **Product Specification**

Maaterial: Cement, Crushed Stone, Sands And So On

· Application: Building Works, Construction

Projects, bridges, docks, airport

Automatic PLC Control,totally Automatic Control System:

• Productivity:

JS1000 Twin-shaft Concrete Mixer Mixer:

• Warranty: 12 Months • Condition:

 After-sales Service Engineers Available To Service Machinery Provided:

Overseas, Online Support, Video Technical Support, Field Installation, commissioning And

Training

• Highlight: Hzs60 Concrete Batching Plant,

Ready Mixed Concrete Batching Plant, 60 Cbm/H Concrete Batching Plant



#### More Images



#### **Product Description**

High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant High Efficiency 60m3/h Stationary Concrete Batching Plant Concrete Mixing Plant

**HZS60 concrete mixing plant** is a high-efficiency and reliable machine designed for large-scale construction projects. It's capable of producing up to 60 cubic meters of concrete per hour, making it ideal for infrastructure projects, commercial buildings, and industrial facilities.

UPS, stable performance Siemens PLC, high speed and precision weighing unit module combined with our professional control and monitoring software;

Full automatic and easy operated production process of material measurement, transfer, mixing and discharging.

Heating system and ice plant could be adopted into this concrete plant in severely cold and hot environment.

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600- 2000)≤±2%	(700-2400)≤±2%	(1000- 3600)≤±2%	(1600- 4800)≤±2%	(1600- 4800)≤±2%
Measuring range and precision of cement	(300- 1200)≤±1%	(300-1200)≤±1%	600- 1800)≤±1%	(800- 2400)≤±1%	(800- 2400)≤±1%
Measuring range and precision of coal ash	(200- 600)≤±1%	(200-600)≤±1%	(300- 900)≤±1%	(400- 1200)≤±1%	(400- 1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200- 700)≤±1%	(360- 1200)≤±1%	(360- 1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



#### Features of concrete batching plant:

- 1.It adopts combined structure and unitized module, which is short, quick and very convenient for installation and demolition .
- 2. Increase the unloading angle of the aggregate bin to solve the problem of unloading difficulties caused by rain
- 3.It is convenient and quick to use the cylinder discharge or electric push rod to discharge.
- 4.The overall steel structure of the mixing station is made of high-quality steel, which has high overall structural strength and strong stability.
- 5. The mixing machine adopts the twin-shaft forced mixing main machine, which has strong mixing performance, uniform mixing and high productivity.
- 6.Excellent pneumatic components, electrical components, etc.; to ensure the reliability of the equipment, accurate metering performance.
- 7. Each maintenance and repair site is provided with a walking platform or a check ladder, and has sufficient operation space.

Easy maintenance and repair 8. Environmental protection and energy saving, using pulse dust removal, recycling waste-water

# 与宣介智工 Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276

amy@hnsunny.com.cn

sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province