



Hzs60 60m3/H Container Type Concrete Batching Plant for Sale

Our Product Introduction

for more products please visit us on sunnyconcretebatchingplant.com

Basic Information

- Place of Origin: Hunan
- Brand Name: SUNNY
- Model Number: HSZ60
- Minimum Order Quantity: 1 set
- Price: USD 110000-150000/ SET
- Packaging Details: container
- Delivery Time: 25-30 days
- Payment Terms: L/C,T/T,D/P,Western Union,MoneyGram
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Maaterial: Cement, Crushed Stone, Sands And So On
- Application: Building Works,Construction Projects,bridges,docks,airport
- Control System: Automatic PLC Control,totally Automatic
- Productivity: ≤60m3/h
- Mixer: JS1000 Twin-shaft Concrete Mixer
- Warranty: 12 Months
- Condition: New
- After-sales Service Provided: Engineers Available To Service Machinery Overseas,Online Support,Video Technical Support,Field Installation,commissioning And Training
- Highlight: **Hzs60 Concrete Batching Plant, Ready Mixed Concrete Batching Plant, 60 Cbm/H Concrete Batching Plant**



Product Description

High Efficiency 60m³/h Stationary Concrete Batching Plant Concrete Mixing Plant
High Efficiency 60m³/h Stationary Concrete Batching Plant Concrete Mixing Plant

Automated Control: Advanced **PLC control system** with user-friendly interface for smooth operation.

Durable Components: Built with high-quality materials, ensuring long service life and reduced maintenance costs.

Environmental Protection: Designed with **dust collection and noise reduction systems** to meet environmental standards.

| Name of parameter | HZS60 | HZS90 | HZS120 | HZS180 | HZS240 |
|--|----------------------|----------------------|-----------------------|-----------------------|----------------------|
| Theoretical productivity | 60 M ³ /h | 90 M ³ /h | 120 M ³ /h | 180 M ³ /h | 240m ³ /h |
| Model of mixer | JS1000 | JS1500 | JS2000 | JS3000 | JS4000 |
| Mixing motor power | 2x18.5Kw | 2x30Kw | 2x37Kw | 2x55Kw | 2*75Kw |
| Cycle period | 60s | 60s | 60s | 60s | 60s |
| Volume of mixer | 1000L | 1500L | 2000L | 3000L | 4000L |
| Unloading height | 4.0m | 4.0m | 4.0m | 4.0m | 4.0m |
| Measuring range and precision of aggregate | (600-2000)≤±2% | (700-2400)≤±2% | (1000-3600)≤±2% | (1600-4800)≤±2% | (1600-4800)≤±2% |
| Measuring range and precision of cement | (300-1200)≤±1% | (300-1200)≤±1% | 600-1800)≤±1% | (800-2400)≤±1% | (800-2400)≤±1% |
| Measuring range and precision of coal ash | (200-600)≤±1% | (200-600)≤±1% | (300-900)≤±1% | (400-1200)≤±1% | (400-1200)≤±2% |
| Measuring range and precision of water | 200-600)≤±1% | (200-600)≤±1% | (200-700)≤±1% | (360-1200)≤±1% | (360-1200)≤±1% |
| Measuring range and precision of admixture | 20-60)≤±1% | (20-60)≤±1% | (30-100)≤±1% | (36-120)≤±1% | (36-120)≤±1% |



Features of concrete batching plant:

1. It adopts combined structure and unitized module, which is short, quick and very convenient for installation and demolition .
2. Increase the unloading angle of the aggregate bin to solve the problem of unloading difficulties caused by rain
3. It is convenient and quick to use the cylinder discharge or electric push rod to discharge.
4. The overall steel structure of the mixing station is made of high-quality steel, which has high overall structural strength and strong stability.
5. The mixing machine adopts the twin-shaft forced mixing main machine, which has strong mixing performance, uniform mixing and high productivity.
6. Excellent pneumatic components, electrical components, etc.; to ensure the reliability of the equipment, accurate metering performance.
7. Each maintenance and repair site is provided with a walking platform or a check ladder, and has sufficient operation space. Easy maintenance and repair
8. Environmental protection and energy saving, using pulse dust removal, recycling waste-water for reuse



Hunan Sunny Intelligent Machinery Co.,LTD.



+86 19118921276



amy@hnsunny.com.cn



sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province