

Hunan

SUNNY

container

25-30 days

USD 110000-150000/ SET

20 Set/Sets per Month

High Quality Hzs180 180cbm/H Concrete Plant

Basic Information

- Place of Origin:
- Brand Name:
- HSZ180 Model Number: 1 set
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Maaterial:
- Application:
- Control System:
- Productivity:
- Mixer:
- Warranty:
- Condition:
- After-sales Service Provided:

Cement, Crushed Stone, Sands And So On Building Works, Construction

L/C,T/T,D/P,Western Union,MoneyGram

- Projects, bridges, docks, airport
- Automatic PLC Control,totally Automatic
- ≤180m3/h
 - JS3000 Twin-shaft Concrete Mixer
- 12 Months
- New
- Engineers Available To Service Machinery Overseas, Online Support, Video Technical Support, Field Installation, commissioning And Training



Product Description

HZS180 Central beton factory full automatic concrete plant 50-120 m3/h wet mix beton framework concrete batching plant p HZS180 Manufacturer Concrete Batch Plant concrete batching plant

Belt Conveyor Type Concrete Batching Plant mainly consists of 5 major systems such as mixer, material weighing system, material conveying system, material storage system and control system and other ancillary facilities. It is equipped with the storage, batching, conveying, stirring, control and other devices of various raw materials required for precast concrete, and various aggregates, powders, admixtures, water, etc. A complete set of equipment for supplying concrete in a concentrated manner than by a mixer. pecification

Key Features:

✓ High Productivity – Produces up to 180 cubic meters of concrete per hour, ensuring fast project completion.

✓ Fully Automatic Control – Advanced PLC system ensures precise batching, mixing, and operation with minimal manual intervention.

- ✓ Modular Design Easy installation, relocation, and expansion for flexible project requirements.
- ✓ Durable Components High-quality mixers, conveyors, and silos ensure long-term reliability.
- ✓ Energy Efficient Optimized design reduces power consumption while maintaining high output.
- ✓ Wide Material Compatibility Works with cement, sand, aggregates, and admixtures for various concrete grades.

Name of parameter	HZS60	HZS90	HZS120	HZS180	HZS240
Theoretical productivity	60 M3/h	90 M3/h	120 M3/h	180 M3/h	240m³/h
Model of mixer	JS1000	JS1500	JS2000	JS3000	JS4000
Mixing motor power	2x18.5Kw	2x30Kw	2x37Kw	2x55Kw	2*75Kw
Cycle period	60s	60s	60s	60s	60s
Volume of mixer	1000L	1500L	2000L	3000L	4000L
Unloading height	4.0m	4.0m	4.0m	4.0m	4.0m
Measuring range and precision of aggregate	(600- 2000)≤±2%	(700-2400)≤±2%	(1000- 3600)≤±2%	(1600- 4800)≤±2%	(1600- 4800)≤±2%
Measuring range and precision of cement	(300- 1200)≤±1%	(300-1200)≤±1%	600- 1800)≤±1%	(800- 2400)≤±1%	(800- 2400)≤±1%
Measuring range and precision of coal ash	(200- 600)≤±1%	(200-600)≤±1%	(300- 900)≤±1%	(400- 1200)≤±1%	(400- 1200)≤±2%
Measuring range and precision of water	200-600)≤±1%	(200-600)≤±1%	(200- 700)≤±1%	(360- 1200)≤±1%	(360- 1200)≤±1%
Measuring range and precision of admixture	20-60)≤±1%	(20-60)≤±1%	(30-100)≤±1%	(36-120)≤±1%	(36-120)≤±1%



Features of concrete batching plant:

High Production Capacity: The HZS180 concrete mixing plant has a theoretical production capacity of 180 cubic meters per hour. This high capacity allows for efficient and continuous production of large volumes of concrete, ensuring timely completion of demanding construction projects.

Advanced Mixing System: The plant is equipped with a twin-shaft concrete mixer, which ensures thorough and efficient mixing of aggregates, cement, water, and additives. The twin-shaft mixer operates at a high speed, delivering a homogeneous mixture with excellent consistency and quality.

Precise Weighing and Dosing: The HZS180 batching plant utilizes advanced weighing systems for accurate measurement and dosing of materials. It includes precision sensors and load cells that ensure precise weighing of aggregates, cement, water, and additives. This precise control of material ratios results in consistent and high-quality concrete mixes.

Modular Design and Easy Installation: The HZS180 batching plant features a modular design, which simplifies its installation, transportation, and relocation. The plant consists of multiple modular units that can be easily assembled and disassembled, reducing setup time and allowing for efficient deployment to different job sites.

Q: What's your after-sale service?

A:12 months warranty for main parts since departure. On-site installation, debugging, workers training. Make sure that your workers operate properly and know daily maintenance well. Q:What's your delivery time?

A:The goods will be delivered in 30-45 days after the 30% of the total amout is paid as deposit, and maybe a little longer if busy in the factory.

B: Generally it is 7-10 days if the goods are in stock. or it is 15-20 days if the goods are not in stock, it is according to quantity.

Q. How long do you warranty your concrete batching plant?

A:We shall guarantee that the commodity for 1 year, excluding the wearing parts, and we will offer our customers the wearing parts all the time with favorable price.

Q: What should I do if I experience a problem on our equipment?

A: You could email us the photos to show what happens or call us, and our service line is available 24/7, and then we will feedback you immediately. Also on-site technician service available as request.

Q.How can we install the plant?

A:Our engineer will make installation drawing before we send the machine, and our engineer will go oversea to guide and train the installation after everything is already set in customer's construction site.

Q: Do you have CE certificate for your concrete batching plant?

A: Yes, we have. It is our patent products, certificated by CE.

특히함 Hunan Sunny Intelligent Machinery Co.,LTD.

+86 19118921276 amy@hnsunny.com.cn sunnyconcretebatchingplant.com

Construction Machinery Supporting Industrial Park, High-tech Zone, Ningxiang City, Hunan Province